

Karakteristika sesalne enote po IEC 60312
Vacuum cleaner motor performance in accordance with IEC 60312

Napetost / Voltage: 120 V

Frekvenca / Frequency: 60 Hz

Nazivna moč / Nominal Power: 1700 W

Napetost Voltage V/Hz	Premer odprtine Orifice mm	Tok Current A	Vhodna moč Input Power W	Vrtljaji Speed min ⁻¹	Podtlak Pressure kPa	Pretok Air Flow dm ³ /s	Zračna moč Air power W	Izkoristek Efficiency %
120/60	50	15,79	1808,12	22364	1,97	66,72	131,22	7,26
120/60	40	15,71	1798,59	22401	4,30	62,78	269,73	15,00
120/60	30	15,62	1789,83	22451	10,00	53,10	530,90	29,66
120/60	23	15,22	1745,89	22798	16,58	39,53	655,32	37,54
120/60	19	14,43	1661,80	23553	19,91	29,34	584,09	35,15
120/60	16	13,55	1569,76	24437	22,33	21,94	489,86	31,21
120/60	13	12,63	1468,25	25507	24,60	15,16	372,79	25,39
120/60	10	11,68	1365,67	26799	26,58	9,33	247,92	18,15
120/60	6,5	10,55	1239,72	28469	27,78	4,07	113,14	9,13
120/60	0	9,68	1141,55	29931	28,77	0,00	0,00	0,00

Mejne vrednosti / Guaranteed values:

Srednja moč / Mean power: $P_{mmin} \geq 1445 \text{ W}$

Podtlak / Vacuum: $p_{max} \geq 27,3 \text{ kPa}$

Pretok pri $\phi 50$ / Air Flow at $\phi 50$: $Q_{\phi 50} \geq 63 \text{ dm}^3/\text{s}$

Zračna moč / Air Power: $P_{2max} \geq 620 \text{ W}$

Izkoristek / Efficiency: $\eta_{max} \geq 36 \%$

Masa / Mass: $m = 2,58 \text{ kg}$

					datum	ime	naziv KARAKTERISTIKA SESALNE ENOTE VACUUM CLEANER MOTOR PERFORMANCE	
				izdelal	20.10.2008	J. Megušar		
				pregledal	30.10.2008	B. Benedičič		
							koda KA 491.3.725	list 5
A0	8779	30.10.2008	J. Megušar					stran 1
ozn.	št. obvestila	datum	ime	Otoki 21, 4228 Železniki, Slovenija			pripadnost	namesto